



FAA-E-2382
AMENDMENT-2
September 2, 1969
SUPERSEDING
AMEND.-1, 5/14/69

DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION SPECIFICATION

RADAR/BEACON BUFFER AMPLIFIERS AND PRETRIGGER GENERATOR

This amendment forms a part of FAA-E-2382 dated January 28, 1969.

Page 2, paragraph 2.1.1: Add the following:

"FAA-G-2100/5 Part 5, Requirements for Equipment Employing
Microelectronic Devices".

Page 5: Delete paragraphs 3.3.1.1.1 and 3.3.1.1.2.

Page 6, paragraph 3.4: Add the following at the end of the paragraph:

"Input and output connectors and terminals shall be accessible
from the rear of the card rack unit. Monitor jacks and adjustable
controls shall be accessible from the front of the unit."

Page 7, paragraph 3.6.1: In the last line of the paragraph delete "450"
and substitute "1500".

Page 7, paragraph 3.6.2: Opposite "e" delete "450" and substitute "1500".

Page 8, paragraph 3.7.1: In the last line of the paragraph delete "450"
and substitute "1500".

Page 8, paragraph 3.7.3: In the second line of the paragraph add "(within 30 nanoseconds)" between the words "identical" and "in". On page 9, opposite "f" change "1.0 nanosecond" to "10.0 nanoseconds".

Page 10, paragraph 3.8.3: In the second line of the paragraph add "(within 30 nanoseconds)" between the words "identical" and "in". Opposite "f" change "1.0 nanosecond" to "10.0 nanoseconds".

Page 11, paragraph 3.9.2.3: In line 2, change the word "input" to "output".

Page 11, paragraph 3.9.3: At the end of line 6 after the word "Any" add "common mode (AC voltage in series with input signal or induced by ground loop currents)".

* * * * *